



US 20040152490A1

(19) **United States**(12) **Patent Application Publication** (10) Pub. No.: **US 2004/0152490 A1**
Aoyama et al. (43) Pub. Date: **Aug. 5, 2004**(54) **RADIO BASE STATION APPARATUS AND
RADIO TRANSMITTING METHOD**

Publication Classification

(76) Inventors: **Takahisa Aoyama, Yokohama-shi (JP);
Kenichi Miyoshi, Yokohama-shi (JP)**(51) Int. Cl.⁷ **H04M 1/00**
(52) U.S. Cl. **455/560; 455/562.1**Correspondence Address:
**Stevens Davis
Miller & Mosher
Suite 850
1615 L Street NW
Washington, DC 20036 (US)**(57) **ABSTRACT**

Directivity control is executed during transmission such that the directivity pattern of the S-CPICH (Secondary Common Pilot Channel) and the directivity pattern of the DSCH (Downlink Shared Channel) are oriented in different directions. That is, the directivity pattern of a known signal is made oriented in a different directions than the directivity pattern of packet data. As a result, interference between the S-CPICH and the DSCH is restrained, so as to make a communication terminal apparatus capable of accurate channel quality detection. At a base station, based on the result of this channel quality detection, the priority of a data packet transmitted by the DSCH is determined.

(21) Appl. No.: **10/479,229 - filed 12/1/03**(22) PCT Filed: **Mar. 4, 2003**(86) PCT No.: **PCT/JP03/02457**(30) **Foreign Application Priority Data**

Mar. 7, 2002 (JP) 2002-062129

